

Double operational amplifier configuration High quality and low tolerance components Subsonic filter

Three different toroidal transfomers to supply digital section and left and right analog sections

Film capacitors used for RIAA curve equalization

MM input's capacitance and resistance regulation

MC input's resistance regulation

Designed and handcrafted in Italy



AUDIO ANALOGUE soundpleasure

AAPHONO MM/MC PHONO PREAMPLIFIER





The new AAphono preamplifier is the latest product of PureAA line.
Just like the AAcento amplifier, it is a product that perfectly fits in the
Audio Analogue philosophy: simple design, highest level sound performances,
great care for the finish and for the materials and parts selection,
together with a remarkable ease of use, make it a perfect partner
for turntables and cartridges of any kind and quality level,
giving in this way the opportunity to listen your beloved vinils in the best way.
AAphono set-up is very easy, can be done simply pushing the configuration's
corresponding buttons under the unit, just behind the front panel, without
removing anything or without using many different switches.
The selected configuration will remain settled also when the
unit will be switched off or disconnected by the power network.





TECHNICAL SPECIFICATIONS

Parameter	Measurement conditions	Value
Channels:		2
Max output voltage	1kHz	7 Vrms
Gain	MM, 1KHz	40 dB
	MC, 1KHz	65 dB
Frequency response	+/-0,25db	10 Hz - 20kHz
	subsonic filter ON(-3dB @ 20Hz)	20 Hz – 20 kHz
Signal/noise ratio	MM, 20Hz-20kHz, A weighted	85dB
	MC, 20Hz-20kHz, A weighted	65dB
Dimensions(HxWxD)		87x220x372mm
Weight		5.8kg





